



WL7 Firewall™

Stylish design, high-tech features and a plentiful source of ice-cold purified water

Unrivalled performance from the world-class point-of-use (POU) water system

This advanced POU water purification system combines refined engineering and high-tech features in a robust and reliable machine. The WL7 Firewall™ (WL7 FW) can dispense up to five varieties of water, including a large volume of refreshing, ice-cold sparkling water. Ideal to satisfy all the hydration needs of even the busiest workplaces.

Leading technology

The WL7 FW features four core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards by IAPMO R&D, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



Firewall purification

Waterlogic's patented and certified Firewall UVC purification system thoroughly purifies the water all the way through to the point of dispense, for microbiologically safe water. Guaranteed free from: up to 99.9999% bacteria, 99.99% viruses and 99.9% cysts.



BioCote® antimicrobial protection

The WL7 FW key surfaces are infused with BioCote®, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross-contamination.



Ice Bath cooling technology

The Ice Bath water cooling system delivers high volumes of ice-cold water, offering the most consistently cold water output of the Waterlogic range.



Industry leading user experience

Designed to offer 'best-in-class' user experience, the WL7 FW features a large dispense area, alongside a user friendly screen interface and water selection dial, allowing users to easily choose between five types of water.



*R600a gas available on 220/240v models only

Features

NSF 55 Class A and NSF P231 certified Firewall, patented UVC technology, that reduces the risks of viruses and pathogenic bacteria, purifying the water up to 99.9999%

Sparkling system, engineered to deliver supreme quality of ice-cold carbonated water, comparable to even the finest bottled water

User interface with 5" full colour LED display featuring machine status bar and water dispensing options

The ergonomic dispense area can accommodate tall water vessels and sports bottles

Maximum service efficiency, achieved via the self diagnostic system and QR code for instant access to the service manual via smart device













Versatile base cabinet converts the unit from countertop to freestanding, and offers filter and CO₂ storage space

Filter and UV fault indicators, as well as other system diagnostics for peace of mind

Leak prevention system provides extra protection and reduces the risk of accidents

Programmable energy saving sleep mode to significantly reduce power consumption when the unit is not in use

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					
3					

Number of users 50+

Technical specifications

Types available

Freestanding (with base cabinet) and countertop

Dimensions

Freestanding
399 mm/15.70" (W) x 1269 mm/50" (H) x 519 mm/20.50" (D)

Countertop
381 mm/15" (W) x 427 mm/17" (H) x 519 mm/20.50" (D)

Dispensing area height

273 mm/10.74"

Weight

47 Kg (103 lbs) freestanding
30 Kg (66 lbs) countertop

Filtration options*

1 x Carbon Block (CBC), certified to NSF/ANSI-53 for cysts asbestos reduction; (CBC for cysts, asbestos and lead reduction are also available)

1 x Granular Activated Carbon (GAC), certified to NSF/ANSI-42;

Optional reverse osmosis (RO) system (Freestanding version only)

* dependent on local water conditions

Storage capacity

Cold only: 4.5 litres (1.2 gal)
Cold and sparkling: 3.8 litres (1 gal)

Storage capacity

Hot: 1.5 litre (0.4 gal)

Dispensing capacity (Cold only)

Up to 17 L (4.5 gal)/h
below 8°C

Dispensing capacity (Cold and sparkling)

Sparkling: Up to 14 L (3.7 gal)/h
below 8°C
Cold: Up to 15 L (4.0 gal)/h

Compressor

USA compressor (R134a): 97W

Compressor

EU compressor (R600a): 100W

Water temperature output

Cold: 5°C/41°F

Hot: 75-93°C/167-199.4°F

Extra hot: 80-95°C/176-203°F

Contact us today

United Kingdom
www.waterlogic.co.uk
+44 (0) 333 323 2307
info@waterlogic.co.uk

Ireland
www.waterlogic.ie
+353 1466 0133
info@waterlogic.ie

USA and Canada
www.waterlogicsusa.com
+1402 905 2001
customerservice@waterlogicsusa.com

Rest of the world
www.waterlogic.com
+353 1293 1960
exportsales@waterlogic.com

Tested and certified



Firewall technology is certified by IAPMO R&T to **NSF/ANSI 55 Class A, NSF P231, US EPA Microbiological Guide Standard, NSF/ANSI 372 and CSA B483.1.**

*certificate may vary depending on different models or products